

VCC-5000-5MP

IP Surveillance
Equipment

HD-SDI / 3G-SDI
Equipment

AHD / TVI / CVI
Equipment

HDMI / VGA
Equipment

Speed Dome Camera

Matrix Switcher Solutions



Network BOX Camera

VCC-5000-5MP



Description Features:

- * 1/2.5" 5.0Megapixel Progressive Scan CMOS Sensor
- * H.264/ MJPEG video compression and JPEG image capture
- * Support dual-stream encoding
- * 5.0MP (2592x1920)
- * C/CS Mount Auto Iris lens
- * ICR true Day/Night
- * Alarm I/O, RS485 interface
- * Max 32GB Hot-swap TF card for local storage
- * POE Support(Optional)



Video Access Technology Corp.

4F.-11, No.6, Lane 609, Sec. 5, Chongxin Rd., Sanchong Dist., New Taipei City, Taiwan (Tong Cheng Industrial Zone)

Tel: +886-2-2999-8383 Fax: +886-2-2999-0303

web : www.videoaccess.com

VCC-5000-5MP

	Specification	VCC-5000-5MP
System	Operating System	Embedded LINUX
	Capacity	Simultaneous remote monitoring, local recording and remote control
	User Interface	WEB, CMS, NVR
Camera	Image Sensor	1/2.5" 5.0Megapixel Progressive Scan CMOS Sensor
	Effective Pixels	2592(H)×1920(V)
	Electronic Shutter	1/5s to 1/50,000s
	Mini. Illumination	Color:0.1Lux/F1.2 ; B/W:0.005Lux/F1.2
	Signal Noise Ratio	>50dB
	Gain Control	Auto/Manual
	White Balance	Auto/Manual
	Day/Night Mode	Auto, dual IR-Cut filter
	WDR Dynamic Range	DWDR
	Lens Type	C/CS Type / Support Auto Iris
Video	Video Compression	H.264/MJPEG Optional
	H.264 Encode Type	H.264 Baseline/H.264 Main Profile/H.264 High Profile Optional
	Image Resolution	5.0Mp/3.0Mp/1080P / 720P / D1
	Encoding Speed	Main Stream : 5.0Mp /10fps, 3.0Mp /20 fps , 1080P/720P30fps/25fps)
		Extra Stream : D1/CIF:(1~30fps/25fps)
	Video Bit Rate	Main Stream : 200Kbps~12Mbps
		Sub Stream : 100Kbps~6Mbps
	Video Format	NTSC/PAL
	Analog Video Output	1 channel BNC (1.0Vp-p, 75Ω)
Network	Ethernet	RJ-45 (10/100Base-T)
	Network Protocol	IPv4/IPv6、RTSP/RTP/RTCP、TCP/UDP、HTTP、DHCP、DNS、FTP、DDNS、PPPoE、SMTP
	Onvif	ONVIF Ver.2.4
	Max User Access	10 users
	Smart phone	Iphone , Ipad ,Android
	Remote Operation	Monitor, System setting, Log information,Maintenance & Upgrade.
Infrared	IR Illuminators	-
	IR Distance	-
Audio	Audio Compression	G.711a/G711u Optional
	Audio Bit Rate	G.711a(8kbps)/G.711u(8kbps)
	Audio Input	1-channel 3.5mm audio interface MIC IN/Line IN
	Audio Output	1-channel 3.5mm audio interface (line level ,600Ω)
Auxiliary	Reset Input	One Reset Button(Hold on 3 seconds at least)
Interface	SD Card	Max 32GB, local storage
	RS485	Yes
	Alarm Input	1-channel input ,N.O /N.C modes adjustable
	Alarm Output	1-channel output ,120VAC 1A/24VDC 1A
General	Power Supply	DC12V
	PoE	- / IEEE802.3af(VCC-5000-5MP-P)
	Power Consumption	<3W
	Working temperature	-10℃~+60℃
	Working humidity	10%~90%
	Dimensions(mm)	150.2mm×77.7mm×55.8mm