

HDMI to 6G-SDI Converter (4K)

VCF-009S

IP Surveillance
Equipment

HD-SDI / 3G-SDI
Equipment

AHD / TVI / CVI
Equipment

HDMI / VGA
Equipment

Speed Dome Camera

Matrix Switcher Solutions



Features

- * Support all type HDMI input signals
- * 1 HDMI in, 2 SDI out, 1 Audio in
- * Support HDMI 4k2k 30Hz
- * Support Analog Stereo 2CH signal input

Specification	VCF-009S
Model	HDMI To 6G-SDI Signal Converter
Input Interface	HDMI x 1
SDI Output Signal Type	SD-SDI(270Mbps), HD-SDI(1.485Gbps),3G-SDI(2.97Gbps), 6G-SDI (5.94Gb/s, 5.94/1.001Gb/s)
Support Output Format	SD:525i@ 59.94Hz,625i@ 50Hz HD:720p@ 23.98Hz/ 24Hz/ 25Hz/ 29.97Hz/ 30Hz 720p@ 50Hz/ 59.94Hz/ 60Hz 1080i@50Hz/59.94Hz/ 60Hz 1080p@ 23.98Hz/ 24Hz/ 25Hz/ 29.97Hz/ 30Hz 3G:1080p@ 50Hz/ 59.94Hz/ 60Hz 6G: 3840x2160,4096x2160@23.98Hz/24Hz/25Hz/30Hz
Audio Input	1x L/R Audio In [3.5mm Stereo Mini-jack]
Max.Input Coax Length	Belden1694A SD-SDI 400 Meters HD-SDI 200 Meters 3G-SDI 140 Meters 6G-SDI 60 Meters
Output Interface	SDI x 2
Color Space	YCbCr 4:2:2
Color Depth	10-bit
Power Supply	12VDC
Power Consumption	3~6Watts
Operating Temperature	-10°C~60°C/14°F~140°F
Storage Temperature	-30°C~70°C/-22°F~158°F
Relative Humidity	20~90%RH(Non-condensation)
Dimension	138mm (W) x 83.5mm (D) x 18mm (H)
Weight	300g

Video Access Technology Corp.

4F.-11, No.6, Lane 609, Sec. 5, Chongxin Rd., Sanchong Dist., New Taipei City, Taiwan (Tong Cheng Industrial Zone)
Tel:+886-2-2999-8383 Fax:+886-2-2999-0303
web : www.videoaccess.com