

VGA ENCODER (H.265)

**VMI-VN001-HD
VGA ENCODER**



Features

- * VGA loop out Support
- * The video screen can be rotated according to angle and cropped according to coordinates
- * Maximum resolution frame rate: 1080p 60Hz
- * Encoding format: H.265, H.264, M-JPEG
- * Low-latency private : 200 ms
- * Video protocol: RTMP/RTSP/HTTP TS/HTTP FLV/HLS/UDP multicast/RTP multicast
- * Support Onvif search and browse video docking with NVR
- * Audio: 3.5mm external audio input/output, supports stereo
- * Configure parameters and upgrade firmware through WEB

Specifications	VMI-VN001-HD
Model	VGA ENCODER (H.265)
Video Input	VGA x 1
Video Output	VGA x 1
Video Encoding / Encoding type	H.265, H.264, M-JPEG
Bitrate(Kbit)	Adjustable
VGA Input Support	1920x1080 60, 50, 30, 25Hz, 1680x1056, 1280x720, 1024x576, 850x480, 720x576, 720x540, 720x480, 720x404, 704x576, 640x480, 640x360, 608x448, 544x480, 480x480, 480x384, 480x360, 480x320, 480x272, 480x270, 400x320, 400x224, 352x480, 352x228, 320x256, 320x240, 320x180, 240x180, Same as the input
Video Compression Standard	High Profile, Main Profile, Base Line
Streaming adjustments	CBR / VBR Adjustable
Media Transmission Protocols	RTMP, RTSP, TS, FLV, HLS, UDP Multicast, RTP Multicast
Audio Encoding	AAC, MP3, MP2, AC3 Adjustable
Audio encoding sample rate	44100 ~ 48000 Adjustable
Audio Video	AAC: 48000 ~ 320000 Adjustable
Audio bitrate	MP3: 64000 ~ 320000 Adjustable MP2: 64000 ~ 320000 Adjustable AC3: 40000 ~ 640000 Adjustable
Volume	Adjustable
Ethernet Port	1000 Mbps
Network configuration	Web settings
ONVIF	Support
Power Supply	12VDC 2A
Power Consumption	5W
Operating Temperature	-20°C ~ 60°C, Humidity 90% or less (non-condensing)
Dimensions	181 x 102 x 35 mm
Weight	455g



Video Access Technology Corp.

4F.-11, No.6, Lane 609, Sec. 5, Chongxin Rd., Sanchong Dist., New Taipei City, Taiwan (Tong Cheng Industrial Zone)

Tel:+886-2-2999-8383 Fax:+886-2-2999-0303

web : www.videoaccess.com

BENESTON® | Data Sheet

IP Surveillance Equipment

HD-SDI / 3G-SDI Equipment

AHD / TVI / CVI Equipment

HDMI / VGA Equipment

Speed Dome Camera

Matrix Switcher Solution