


VCF-1003DA-P

Features



- * SD/HD/3G-SDI 1 to 3 Distribution Amplifier
- * SD-SDI(270Mbps), HD-SDI(1.485Gbps), 3G-SDI(2.97Gbps)
- * Built-in Cable Equalizer, Re-clocker & Cable Driver
- * Max. cable length : SD-SDI 150m, HD-SDI 120m, 3G-SDI 100m
- * Excellent SDI signal jitter suppression function
- * Power supply and SDI signal format indicator
- * Embedded ESD to protect the circuit
- * Audio Support

Specification	VCF-1003DA-P
MODEL No.	1CH Input 3CH Output SDI Signal Distribution Amplifier
Video In	1 x BNC (75 Ohm, SDI)
Video Out	3 X BNC (75 Ohm, SDI)
Video Bandwidth	SD-SDI (270Mbps), HD-SDI (1.485Gbps), 3G-SDI(2.97Gbps)
Input Format	SD-SDI: 525i_59.94, 625i_50 HD-SDI: 720p_25,30, 50, 59.94, 60 Hz 1080i_50, 59.94, 60 Hz / 1080p_25, 30 Hz 3G-SDI: 1080p_50, 59.94,60 Hz 0.8V p-p
SDI Signal Range	0.8V p-p
SDI Impedance	75 ohms
Max. Distance	Belden 1694A SD-SDI 350 meters ; HD-SDI 180 meters ; 3G-SDI 60 meters
Power Supply	12V DC
Operating Temperature Range	-10°C ~ + 55°C
Storage Temperature Range	-30°C ~ + 65°C
Dimension (I X W X H)	150 x 110 x 25 mm



IP Surveillance Equipment

HD-SDI / 3G-SDI Equipment

AHD / TVI / CVI Equipment

HDMI / VGA Equipment

Speed Dome Camera

Matrix Switcher Solutions