

## HDMI Decoder

### VMS-HE001-HD HDMI Decoder



#### Features

- \* Decode 1 to 4 channels of network video streaming or USB flash drive video, 4 split screen output
- \* Compatible with decoding multiple communication protocols HTTP TS/HLS/FLV/RTSP/SRT/RTMP/ RTMPS/UDP/RTP
- \* Low decoder latency, 80-200ms through local network
- \* Support video decoding format H.265 / H.264
- \* Decoding function: 1 channel decoding 2160P@30, output 1 channel 1080P@60 or 4 sets of channels 1080P@25, output 1 set of channels 1080P@60
- \* Support Onvif to search for network camera RTSP address and decode
- \* CVBS / VGA / HDMI simultaneous video output
- \* Support HDMI built-in audio output (support stereo audio)
- \* Set parameters and upgrade firmware from web browser

#### Specifications

#### VMS-HE001-HD

Media Access	Network Video	Standard Agreement	RTMP/ RTSP /HTTP TS/HTTP FLV/ HLS/SRT/UDP /RTP
		Private Agreement	HTTP PTE/PTL
	USB Video	NTFS/EXFAT/FAT32	WMV/MPEG/MP4/MOV/FLV/F4V
Video decode	Type		H.265/H.264
	frame rate		1~ 60 fps
	Bit rate(k bit)		32-32000
	Resolving power		Maximum support 2160P@30
Audio decode	Number of routes		1~4
	Type		G711A/G711U/AAC+/AAC++/MP2/MP3
	Number of Channels		Single channel/Dual Channel
	Sampling rate		8000/11250/22500/44100/48000 Hz
	Number of routes		1
Video Output	HDMI		1080P@60/1080P@50/1080P@30/1080P@25/ 720P@60/720P@50/576P@50/480P@60
	Color		Brightness, Contrast, Chroma, Saturation
Audio Output	HDMI		48KHz Dual Channel Output
	3.5mm		Dual Channel Output
	Volume		0-80
Common	Enable		Disable / Enable
	Network		1000Mbps
	Configuration		WEB, Upload, Reset
	Power Supply		12V/DC · 2A
	Power		<1W
	Temperature		-20°C~+60°C
	Humidity		<90%, non-condensed
	Size		11.2cm x 15cm x 2.8cm
	Weight		465gs



#### Video Access Technology Corp.

6F.-17, No.14, Lane 609, Sec. 5, Chongxin Rd., Sanchong Dist., New Taipei City, Taiwan (Tong Cheng Industrial Zone) Tel:+886-2-2999-8383 Fax:+886-2-2999-0303

web : [www.videoaccess.com](http://www.videoaccess.com)

**BENESTON®** | Data Sheet

[videoaccess.com](http://videoaccess.com)

IP Surveillance Equipment

HD-SDI / 3G-SDI Equipment

AHD / TVI / CVI Equipment

HDMI / VGA Equipment

Speed Dome Camera

Matrix Switcher Solution