

### VCF-005PH



#### Features

- \* Support all type SDI resolution input
- \* Scaling & Seamless support
- \* Audio Embedding and De-embedding support
- \* Control: PC via USB controll or dip switch
- \* Redundant SDI Input & Re-clocked Output
- \* Remote control by PC via USB

Specification	VCF-005PH
Model	SD/HD/3G-SDI To HDMI & AV Signal Converter
Input Interface	3G-SDI x1,Alt 3G-SDI x1,AES/EBU x1,Analog audio x1
Input Signal Type	SMPTE 292 / 259M / 424M
Support Input Format	1080p 60/59.94/50/30/29.97/25/24/23.98 Hz 1080PsF 30/29.97/25.24/23.98 Hz 1080i 60/59.94/50 Hz 720p 60/59.94/50/30/29.97/25/24/23.98 Hz 625i 50,525i 59.94 Hz
SDI Color Space and Precision	YUV 4:2:2
Output Interface	3G-SDI loop x1 ,HDMI x1,AV x1,AES/EBUx1,Analog audio x1
HDMI Video Output	HDMI TypeA x1
AV Output	3.5mm jack x1
SDI Loop Output	SD/HD/3G-SDI x1
AES/EBU Digital Audio Output	6.35mm TRS jack x1
Analog Audio Output	3.5mm jack x1
HDMI Output Format	1080p 60/50/30/25/24 1080i 60/50 720p 60/50/30/25/24 576i/50,480i 60
HDMI Color space and Precision	YUV 4:2:2 YUV 4:4:4 RGB 4:4:4
AV Output Format	NTSC or PAL
Power Supply	12VDC
Power Consumption	6Watts
Operating Temperature	-10°C~60°C/14°F~140°F
Storage Temperature	-30°C~70°C/-22°F~158°F
Relative Humidity	20~90%RH(Non-condensation)
Dimension	126 x 104 x 25 mm

IP Surveillance Equipment

HD-SDI / 3G-SDI Equipment

AHD / TVI / CVI Equipment

HDMI / VGA Equipment

Speed Dome Camera

Matrix Switcher Solutions