

VIR-410SDI-35Z-H



Description Features:

- * 2.1 Mega Pixel, 1/3" Panasonic CMOS Sensor
- * 1080p(1920x1080)@60/50fps
- * 2.8-12mm 3 Megapixel Lens with ICR
- * Support WDR,3D-DNR,DEFOG
- * OSD menu,Motion detection,Privacy Zone,HLC,BLC
- * True Day/Night Mechanical Lens Filter (ICR)
- * TV Out(BNC) with NTSC/PAL Selectable
- * Dual Output-Megapixel
HD-SDI(BNC)&CVBS:1.0 Vp-p 75Ω
- * 40M IR distance with 42ea Φ5 LED lights
- * External Adjust Zoom/Focus on back panel
- * Cable Through Bracket
- * Water Proof IP 66 rate

Specification	VIR-410SDI-35Z-H
Image Sensor	2.1 Mega Pixel, Panasonic CMOS Sensor
Effective pixels	1920(H) x 1080(V)
Scanning system	Progressive Scan
Minimum illumination	0 Lux(LED ON)
Lens	2.8-12mm 3 Megapixel Lens with ICR
IR view distance	About 40M with 42ea (Φ5) LEDs
WDR	OFF/ON(Level Adjustable)
O.S.D	Built-in
3D-DNR	OFF/ON(LOW/MIDDLE/HIGH)
Sens-Up	OFF/ON
Motion Detection	OFF/ON
Privacy Zone	OFF/ON
HLC	OFF/ON
B.L.C. control	OFF/ON
Defog	OFF/ON
White balance	AWB/ATW/PUSH/MANUAL
A.G.C	HIGH / LOW
Electronic shutter Speed	AUTO/MANUAL/FLK
Video output	HD-SDI(SMPTE 292M compatible)
Operation temperature	-10°C~+50°C
Operation Humidity	Within 95% RH
Power supply	DC12V(+/-15%)
Power Consumption	100mA / IR LED ON:400mA Max
Dimensions	355(L)*110(W)*102(H)mm
Weight	870g

IP Surveillance Equipment

HD-SDI / 3G-SDI Equipment

AHD / TVI / CVI Equipment

HDMI / VGA Equipment

Speed Dome Camera

Matrix Switcher Solutions

Video Access Technology Corp.

6F.- 11, No.14, Lane 609, Sec. 5, Chongxin Rd., Sanchong Dist., New Taipei City, Taiwan (Tong Cheng Industrial Zone)
Tel:+886-2-2999-8383 Fax:+886-2-2999-0303
web : www.videoaccess.com