

NVR-8032S/NVR-8064S

IP Surveillance
Equipment

HD-SDI / 3G-SDI
Equipment

AHD / TVI / CVI
Equipment

HDMI / VGA
Equipment

Speed Dome Camera

Matrix Switcher Solutions

Network Video Recorder

NVR-8032S 32CH NVR

NVR-8064S 64CH NVR



Description Features

- * Embedded Linux operating system
- * H.265/H.264 compression algorithm support dual stream
- * 32CH/64 channel 4K/5MP/4MP/3MP/2MP/720P Recording
- * Display: VGA / HDMI output support
- * 1080P high definition output
- * Onvif agreement with standard
- * 8 HDD Bay , up to 6TB Support(Each)
- * Mobile phone: support : iphone windows mobile blackberry symbian android

Video Access Technology Corp.

4F.-11, No.6, Lane 609, Sec. 5, Chongxin Rd., Sanchong Dist., New Taipei City, Taiwan (Tong Cheng Industrial Zone)

Tel:+886-2-2999-8383 Fax:+886-2-2999-0303

web : www.videoaccess.com

BENESTON® | Data Sheet

videoaccess.com

NVR-8032S/NVR-8064S

IP Surveillance Equipment
 HD-SDI / 3G-SDI Equipment
 AHD / TVI / CVI Equipment
 HDMI / VGA Equipment
 Speed Dome Camera
 Matrix Switcher Solutions

| Specification | | NVR-8032S | NVR-8064S |
|------------------|-----------------------|---|--------------------------------|
| Product Category | t | 32CH Network Video Recorder | 64CH Network Video Recorder |
| System | Compression Format | H.265/H.264 | |
| | System resources | Multiplex real-time video ,multi-channel playback ,multi-channel multiplayer network operation ,the USB backup at same time | |
| | OS | Embedded Linux | |
| | Image decoding | H.265/H.264 | |
| | Playback | 1080P | |
| | Input | 32CH (4K/5MP/4MP/3MP/2MP/720P) | 64CH (4K/5MP/4MP/3MP/2MP/720P) |
| | Output | 1*BNC Outputs,1*VGA,1*HDMI | |
| Audio | Audio compression | G.711A | |
| | Audio Input | 1 | |
| | Audio Output | 1 | |
| Recording | Resolution | Support 4K/5MP/4MP/3MP/2MP/720P | |
| | Recording mode | Manual operation | |
| | Recording Mode | Schedule, Manual, Motion, Sensor | |
| Playback | Video query | Time ,calendar ,event ,and passage retrieval | |
| | Search Mode | Time, Event list | |
| Backup | USB Disk | USB 2.0 USB flash disk ,USB hard disk | |
| Remote | Browser | IE Browser | |
| Application | CMS | support | |
| | User Access | 10 users online with professional authority management | |
| Storage | HDD | 8 SATA HDD ,up to 6TB (each) | |
| PTZ | PTZ | 1*RS485 port, support | |
| | PTZ Control | pan, tilt, zoom, preset, cruise, trace | |
| Network | Ethernet | 10M/100M/1000M adaptable Ethernet interface x2 | |
| | Protocol | TCP/IP, DHCP, DDNS, NTP, SMTP | |
| | Mobile phone | Support Windows OS,Symbian OS,iPhone ,Blackberry and Android operation system Mobile phone | |
| Others | Operating Temperature | -10°C to +55°C | |
| | Humidity | 10% to 90% Humidity | |
| | Dimension(L x W x H) | 2U, 440x450x95 (mm) | |

