

HDMI to AHD Signal Converter

AHD-ER03HR

Description Features:

- * Automatically detect the HDMI EDID information
- * HDMI compatible with HDCP
- * HDMI support : 1.4 version
- * With 1080P / 720P and NTSC/PAL switch to control the AHD output.
- * The output of AHD supports 720P and 1080P 30/25Hz
- * One Channel HDMI loop out (Not support audio & 1080p 30/25Hz output)
- * The HDMI video input supports:
800x600, 1024x768, 1280x720,
1280x1024, 1360x768, 1366x768, 1440x900,
1080i 60/59.94/50Hz
1920x1080P 60/59.94/50/30/25 Hz.
- * When HDMI connection is lost, the Converter transfer a black screen and send text "connection lost" on screen as an alert.



IP Surveillance Equipment
 HD-SDI / 3G-SDI Equipment
 AHD / TVI / CVI Equipment
 HDMI / VGA Equipment
 Speed Dome Camera
 Matrix Switcher Solutions

Specification	AHD-ER03HR
Model	AHD-ER03HR
Input Interface	1x HDMI Signal
Signa Outputl	1x AHD Signal
Support Output Format	720P 60/50Hz or 1080P 30/25Hz
Max. Input Coax Length	400 meters for 1080P
HDMI Loop out	HDMI x 1
HDMI input format	800x600, 1024x768, 1280x720, 1280x768, 1280x960, 1280x1024, 1360x768, 1366x768, 1400x900, 1600x1900, 1600x1024, 1920x1080i, 1920x1080p (60/59.94/50/30/25Hz)
Power Sup ply	DC12V, 1A
Power C onsumption	4~5 Watts
Operating Temperature	-10°C~ 60°C/ 14°F ~ 140°F
Storage Temperature	-30°C ~ 70°C/ -22°F ~158°F
Relative Humidity	20~90% RH (No n-condensaion)
Dimension	128*84*26mm



Video Access Technology Corp.

4F.-11, No.6, Lane 609, Sec. 5, Chongxin Rd., Sanchong Dist., New Taipei City, Taiwan (Tong Cheng Industrial Zone)
 Tel:+886-2-2999-8383 Fax:+886-2-2999-0303
 web : www.videoaccess.com