

### VCF-009H



#### Features

- \* Support all type HDMI resolution input
- \* Audio Embedding and De-embedding support
- \* Control: PC via USB controll or dip switch
- \* Scaling and frame rate support
- \* Remote control by PC via USB

Specification	VCF-009H
Model	HDMI & AV To SD/HD/3G-SDI Signal Converter
HDMI Input	HDMI type A x1
AES/EBU Digital Audio Input	6.35mm TRS jack x1
AES/EBU Digital Audio Output	6.35mm TRS jack x1
AV Input	3.5mm jack x1
Analog Audio Input	3.5mm audio socket x1
Analog Audio Output	3.5mm audio socket x1
HDMI Input Format	1080p 60/59.9450/30/29.97/25/24/23.98/23.973 1080i 60/59.94/50 720p 60/59.94/50/30/29.97/25/24/23.98 576p 50 576i 50 480p 59.94 480i 60/59.94
HDMI Color Space and Precision	YUV 4:2:2 ,YUV 4:4:4 , RGB 4:4:4
AV Input Format	NTSC , PAL
SDI Output	x 3
SDI Output Format	1080p 60/50/30/25/24 Hz 1080i 60/50 Hz 720p 60/50/30/25/24 Hz 625i 50, 525i 60,625i 50_Cut
Output Signal Type	SD-SDI / HD-SDI / 3G-SDI
SDI Compliance	SMPTE 292M / 259M / 424M
Power Supply	12VDC
Power Consumption	6Watts
Operating Temperature	-10°C~60°C/14°F~140°F
Storage Temperature	-30°C~70°C/-22°F~158°F
Relative Humidity	20~90%RH(Non-condensation)
Dimension	126 x 104 x 25 mm / 6.22 x 4.72 x 1.42 inches
Weight	520g

IP Surveillance Equipment

HD-SDI / 3G-SDI Equipment

AHD / TVI / CVI Equipment

HDMI / VGA Equipment

Speed Dome Camera

Matrix Switcher Solutions