

VCD-320H5MPKE

IP Surveillance
Equipment

HD-SDI / 3G-SDI
Equipment

AHD / TVI / CVI
Equipment

HDMI / VGA
Equipment

Speed Dome Camera

Matrix Switcher Solutions

Network Dome Camera

VCD-320H5MPKE



Description Features:

- * 1/2.5" 5.0 Megapixel CMOS image sensor.
- * H.264 / MJPEG video compression and JPEG image capture.
- * 5.0M (2592×1920)
- * Dual encoding streams supported.
- * Lens: 3.6mm Fixed Lend ,
- * True Day / Night ICR.
- * Support DC12V power supply, POE (optional).
- * ONVIF Support.

Video Access Technology Corp.

4F.-11, No.6, Lane 609, Sec. 5, Chongxin Rd., Sanchong Dist., New Taipei City, Taiwan (Tong Cheng Industrial Zone)

Tel:+886-2-2999-8383 Fax:+886-2-2999-0303

web : www.videoaccess.com

BENESTON® | Data Sheet

videoaccess.com

VCD-320H5MPKE

Specification	VCD-320H5MPKE
System	
Operating System	Embedded LINUX
Capacity	Simultaneous remote monitoring, local recording and remote control
User Interface	WEB, CMS, NVR
Camera	
Image Sensor	1/2.5" 5.0Megapixel Progressive Scan CMOS Sensor
Effective Pixels	2592(H) × 1920(V)
Electronic Shutter	1/5s to 1/50,000s
Mini. Illumination	Color:0.1Lux/F1.2 ; B/W:0.005Lux/F1.2
Signal Noise Ratio	>50dB
Gain Control	Auto/Manual
White Balance	Auto/Manual
Day/Night Mode	Auto, dual IR-Cut filter
WDR Dynamic Range	DWDR
Lens Type	3.6mm Fixed Lens /F1.4) M12 mount
Video	
Video Compression	H.265/H.264
H.264 Encode Type	H.264 Baseline/H.264 Main Profile/H.264 High Profile Optional
Image Resolution	5MP/4MP/1080P/720P/D1/CIF
Encoding Speed	Main Stream : 5MP/4MP/1080P/720P(30fps/25fps) Extra Stream : D1/CIF:(1~30fps/25fps)
Video Bit Rate	Main Stream : 200Kbps~12Mbps Sub Stream : 100Kbps~6Mbps
Video Format	NTSC/PAL
Analog Video Output	1 channel BNC (1.0Vp-p, 75 Ω)
Network	
Ethernet	RJ-45 (10/100Base-T)
Network Protocol	IPv4/IPv6、RTSP/RTP/RTCP、TCP/UDP、HTTP、DHCP、DNS、FTP、 DDNS、PPPoE、SMTP
Onvif	ONVIF Ver.2.4
Max User Access	10 users
Smart phone	Iphone , Ipad ,Android
Remote Operation	Monitor, System setting, Log information,Maintenance & Upgrade.
Infrared	
IR Illuminators	-
IR Distance	-
Audio	
Audio Compression	-
Audio Bit Rate	-
Audio Input	-
Audio Output	-
Auxiliary	
Reset Input	One Reset Button(Hold on 3 seconds at least)
Interface	
SD Card	-
RS485	-
Alarm Input	-
Alarm Output	-
General	
Power Supply	DC12V
PoE (optional)	IEEE802.3af(VCD-320H5MPK-P)
Power Consumption	<2.5W
Working temperature	-10℃~+60℃
Working humidity	10%~90%
Dimensions(mm)	119.8mm x 67.5 x Φ62mm