

FULL HD-SDI Bullet IR Camera



VIR-410-SDI / VIR-410-SDI-H



Description Features:

- * 2.1 Mega Pixel, Panasonic Sensor
- * 1080P(1920x1080)@30/25fps
(VIR-410-SDI-H 60/50fps)
- * 3.6mm 3 Megapixel Lens
- * Support WDR,3D-DNR,DEFOG
- * OSD menu,Motion detection,Privacy Zone,HLC,BLC
- * True Day/Night Mechanical Lens Filter(ICR)
- * Dual Output-Megapixel
HD-SDI(BNC)&CVBS:1.0 Vp-p 750hm
- * 20M IR distance with 21ea Φ 5 LED lights
- * Water Proof: IP 66 rate

Specification	VIR-410-SDI/VIR-410-SDI-H
Image Sensor	2.1 Mega Pixel, Panasonic CMOS Sensor
Effective pixels	VIR-410-SDI: 1920(H) x 1080(V) 30/25fps (410-SDI-H: 60/50fps)
Scanning system	Progressive Scan
Minimum illumination	0 Lux(LED ON)
Lens	3.6mm 3 Megapixel Fixed Lens
IR view distance	About 20M with 21ea (Φ 5) LEDs
WDR	OFF/ON(Level Adjustable)
O.S.D	Built-in
3D-DNR	OFF/ON(LOW/MIDDLE/HIGH)
Sens-Up	OFF/ON
Motion Detection	OFF/ON
Privacy Zone	OFF/ON
HLC	OFF/ON
B.L.C. control	OFF/ON
Defog	OFF/ON
White balance	AWB/ATW/PUSH/MANUAL
A.G.C	HIGH / LOW
Electronic shutter Speed	AUTO/MANUAL/FLK
Video output	HD-SDI(SMPTE 292M compatible)
Operation temperature	-10°C - +50°C
Operation Humidity	Within 95% RH
Power supply	DC12V(+/-15%)
Power Consumption	100mA / IR LED ON:400mA Max
Dimensions	138 Φ x 100mm
Weight	650g

IP Surveillance
Video Equipment

HD-SDI / 3G-SDI
Video Equipment

AHD / TVI / CVI
Video Equipment

HDMI / VGA
Video Equipment

Speed Dome Camera
Video Equipment

Matrix Switcher Solutions
Video Equipment