

HDMI Fiber Converter

VMI-SMF01TX/RX



Features:

- * Maximum support 4096x2160_30Hz and downward compatible
- * Support 1 channel HDMI video embedded audio signal
- * HDMI input automatic detection
- * HDMI 1.4 & HDCP 1.4 Support
- * EDID transparent transmission
- * Support DDC CEC HPD signal

Specification	VMI-SMF01TX/RX
Input interface	HDMI male (19Pins HDMI Type Port)
Output interface	HDMI male (19Pins HDMI Type Port)
Optical Type	Wavelength :1310, 1550nm
Max. Distance	0 ~ 20Km
Connector	LC
Transmitted power	> 5dbm
Maximum Receiving Sensitivity	> -14dBm
Support Input Format	4096*2160_30Hz downward compatibility 1080p: 23.98, 24, 25, 29, 30, 50, 59.94, 60 1080i: 50, 59.94, 60 720p: 25, 29.97, 30, 50, 59.94, 60 800x600, 1024x768, 1400x1050, 1366x768, 1440x900, 1600x1200 up to 1920x1200_60
DATA comm. method	None
Power Supply	DC5V
Power Consumption	<1.5 Watts
Power Supply physical connector	Micro-USB
Operating Temperature	-20°C ~ 60°C
Dimensions	80 x 20 x 10.5mm

Video Access Technology Corp.

6F.- 17, No.14, Lane 609, Sec. 5, Chongxin Rd., Sanchong Dist., New Taipei City, Taiwan (Tong Cheng Industrial Zone)
Tel:+886-2-2999-8383 Fax:+886-2-2999-0303
web : www.videoaccess.com